

SAFETY DATA SHEET

Surface Cleaner

Section 1. Identification

GHS product identifier : Surface Cleaner
SDS code : R27624

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use
Uses advised against
All other uses

Supplier's details

Akzo Nobel Coatings, Inc.
 1845 Maxwell
 Troy, MI, 48084
 USA
 (800) 618-1010

Akzo Nobel Coatings Ltd.
 110 Woodbine Downs Blvd.
 Unit #4 Etobicoke, Ontario
 Canada M9W 5S6
 +1 (800) 618-1010

Importer : Cía. Mexicana de Pinturas International
 S.A. de C.V., Carretera Anillo Periférico,
 No Ext 205, No Interior A, Colonia HDA S JOSE, Garcia, Garcia, CP 66000, Nuevo Leon.
 RFC: ANA9510267C4

Emergency telephone number (with hours of operation) : CHEMTREC +1 (800) 424-9300 (Inside the US)
 CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A
 CARCINOGENICITY - Category 2
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
 ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Section 2. Hazards identification

Hazard statements : Flammable liquid and vapour.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of causing cancer.
 May cause damage to organs through prolonged or repeated exposure. (hearing organs)

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Do not breathe vapour. Wash hands thoroughly after handling.

Response : IF exposed or concerned: Get medical advice or attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national or international regulations.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Distillates (petroleum), hydro- treated light	≥25 - ≤50	64742-47-8
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5 through C10 and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).]	≥10 - ≤25	64742-89-8
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (- 4°F to 374°F).]	≥10 - ≤25	64742-49-0
Distillates (petroleum), light distillate hydrotreating process, low-boiling	≥10 - ≤25	68410-97-9
ethyl acetate	≤10	141-78-6
xylene	≤10	1330-20-7
ethylbenzene	≤3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 3/21/2024

Version : 1

Date of previous issue : No previous validation

2/17

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light	ACGIH TLV (United States, 1/2022). [Kerosene] Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.
Solvent naphtha (petroleum), light aliph.	None.
Naphtha (petroleum), hydrotreated light	None.
Distillates (petroleum), light distillate hydrotreating process, low-boiling ethyl acetate	None.
	ACGIH TLV (United States, 1/2022). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens. TWA: 1440 mg/m ³ 8 hours. TWA: 400 ppm 8 hours.
	NIOSH REL (United States, 10/2020). TWA: 1400 mg/m ³ 10 hours. TWA: 400 ppm 10 hours.
	OSHA PEL (United States, 5/2018). TWA: 1400 mg/m ³ 8 hours. TWA: 400 ppm 8 hours.
	OSHA PEL 1989 (United States, 3/1989). TWA: 1400 mg/m ³ 8 hours. TWA: 400 ppm 8 hours.
xylene	ACGIH TLV (United States, 1/2022). [xylene] Notes: 1996 Adoption Substances for which there is a Biological Exposure Index or Indices Refers to Appendix A -- Carcinogens.

Section 8. Exposure controls/personal protection

ethylbenzene

STEL: 651 mg/m³ 15 minutes.TWA: 434 mg/m³ 8 hours.

TWA: 20 ppm 8 hours.

OSHA PEL (United States, 5/2018).**[Xylenes]**TWA: 435 mg/m³ 8 hours.

TWA: 100 ppm 8 hours.

OSHA PEL 1989 (United States, 3/1989).**[Xylenes (o-, m-, p-isomers)]**STEL: 655 mg/m³ 15 minutes.

STEL: 150 ppm 15 minutes.

TWA: 435 mg/m³ 8 hours.

TWA: 100 ppm 8 hours.

ACGIH TLV (United States, 1/2022).**Ototoxicant. Notes: Substances for which there is a Biological Exposure Index or Indices 2002 Adoption.**

TWA: 20 ppm 8 hours.

NIOSH REL (United States, 10/2020).STEL: 545 mg/m³ 15 minutes.

STEL: 125 ppm 15 minutes.

TWA: 435 mg/m³ 10 hours.

TWA: 100 ppm 10 hours.

OSHA PEL (United States, 5/2018).TWA: 435 mg/m³ 8 hours.

TWA: 100 ppm 8 hours.

OSHA PEL 1989 (United States, 3/1989).STEL: 545 mg/m³ 15 minutes.

STEL: 125 ppm 15 minutes.

TWA: 435 mg/m³ 8 hours.

TWA: 100 ppm 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures**Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not applicable. [DIN EN 1262]
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : 77°C (170.6°F)
- Flash point** : Closed cup: 23°C (73.4°F) [Pensky-Martens]
- Flammability** : Not available.
- Lower and upper explosion limit** : Greatest known range: Lower: 2.2% Upper: 11.5% (ethyl acetate)
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethyl acetate	81.59	10.9				
Naphtha (petroleum), hydrotreated light	42.15	5.6	OECD 104	357.48	47.7	OECD 104
ethylbenzene	9.3	1.2				

- Relative vapour density** : Not available.
- Relative density** : 0.756 [ISO 8130-2/-3]
- Solubility(ies)** :
Not available.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** :

Section 9. Physical and chemical properties and safety characteristics

Ingredient name	°C	°F	Method
Distillates (petroleum), hydrotreated light	>220	>428	
Solvent naphtha (petroleum), light aliph.	280 to 470	536 to 878	
Naphtha (petroleum), hydrotreated light	280 to 470	536 to 878	DIN EN 14522

Decomposition temperature : Not available.

Viscosity : Kinematic (room temperature): 13 mm²/s (13 cSt) [DIN EN ISO 3219]
Kinematic (40°C (104°F)): 7 mm²/s (7 cSt) [DIN EN ISO 3219]

(****To be Translated****) : 100% (w/w)

Weight Volatiles

(****To be Translated****) : 100.00 %(v/v)

Volume Volatiles

(****To be Translated****) : 0.00 %(w/w)

Weight Solids

(****To be Translated****) : 0 %(v/v)

Volume Solids

(****To Be Translated****) : 6.3 lbs/gal 756 g/l minus water and exempt solvents

Regulatory VOC

VOC Actual : 6.3 lbs/gal 756 g/l

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10 µm : 0

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure	
Distillates (petroleum), light distillate hydrotreating process, low-boiling	LD50 Oral	Rat	5.17 g/kg	-	
	ethyl acetate	LD50 Oral	Rat	5170 mg/kg	-
		LC50 Inhalation Gas.	Rat	1600 ppm	8 hours
		LC50 Inhalation Vapour	Mouse	45 g/m ³	2 hours
		LD50 Intraperitoneal	Mouse	709 mg/kg	-
		LD50 Oral	Guinea pig	5.5 g/kg	-
		LD50 Oral	Guinea pig	5500 mg/kg	-
		LD50 Oral	Mouse	4.1 g/kg	-
		LD50 Oral	Mouse	4100 mg/kg	-
		LD50 Oral	Rabbit	4935 mg/kg	-
LD50 Oral	Rat	5620 mg/kg	-		
xylene	LD50 Subcutaneous	Guinea pig	3 g/kg	-	
	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours	
	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours	
	LC50 Inhalation Gas.	Rat	6670 ppm	4 hours	
	LD50 Intraperitoneal	Mouse	1548 mg/kg	-	
	LD50 Intraperitoneal	Mouse	1548 mg/kg	-	
	LD50 Intraperitoneal	Rat	2459 mg/kg	-	
	LD50 Oral	Mouse	2119 mg/kg	-	
	LD50 Oral	Rat	4300 mg/kg	-	
	LD50 Oral	Rat	4300 mg/kg	-	
ethylbenzene	LD50 Subcutaneous	Rat	1700 mg/kg	-	
	LC50 Inhalation Gas.	Rabbit	4000 ppm	4 hours	
	LC50 Inhalation Vapour	Mouse	35500 mg/m ³	2 hours	
	LC50 Inhalation Vapour	Rat	55000 mg/m ³	2 hours	
	LD50 Dermal	Rabbit	>5000 mg/kg	-	
	LD50 Dermal	Rabbit	17800 uL/kg	-	
	LD50 Intraperitoneal	Mouse	2624 uL/kg	-	
	LD50 Oral	Rat	3500 mg/kg	-	
	LD50 Oral	Rat	3500 mg/kg	-	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
xylene	-	3	-
ethylbenzene	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
ethyl acetate	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), light aliph.	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1
Distillates (petroleum), light distillate hydrotreating process, low-boiling	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Date of issue/Date of revision : 3/21/2024 Version : 1

Date of previous issue : No previous validation 10/17

Section 11. Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product as-supplied	N/A	20948.4	N/A	169.7	N/A
xylene	N/A	1100	N/A	11	N/A
ethylbenzene	N/A	N/A	N/A	11	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	
Distillates (petroleum), hydrotreated light	Acute LC50 5900 µg/l Fresh water	Fish - Lepomis macrochirus	4 days	
	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days	
	Acute LC50 2400 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days	
	Acute LC50 2600 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days	
	Acute LC50 2900 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	
	Solvent naphtha (petroleum), light aliph. ethyl acetate	Acute EC50 2500000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
		Acute LC50 1600000 µg/l Fresh water	Crustaceans - Asellus aquaticus	48 hours
		Acute LC50 750000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
		Acute LC50 175000 µg/l Fresh water	Daphnia - Daphnia cucullata	48 hours
Acute LC50 154000 µg/l Fresh water		Daphnia - Daphnia cucullata	48 hours	
Acute LC50 560000 µg/l Fresh water		Daphnia - Daphnia magna	48 hours	
Acute LC50 230000 µg/l Fresh water		Daphnia - Daphnia pulex	48 hours	
Acute LC50 295000 µg/l Fresh water		Daphnia - Daphnia pulex	48 hours	
Acute LC50 212500 µg/l Fresh water		Fish - Heteropneustes fossilis	96 hours	
Acute LC50 484000 µg/l Fresh water		Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
Acute LC50 425300 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours		
xylene	Acute LC50 230000 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Chronic NOEC 12 mg/l Fresh water	Daphnia - Daphnia magna	21 days	
	Chronic NOEC 2400 µg/l Fresh water	Daphnia - Daphnia magna	21 days	
	Chronic NOEC 75.6 mg/l Fresh water	Fish - Pimephales promelas - Embryo	32 days	
	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours	

Date of issue/Date of revision : 3/21/2024

Version : 1

Date of previous issue : No previous validation

11/17

Section 12. Ecological information

ethylbenzene	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute LC50 15700 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 20870 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 5400 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 4900 µg/l Marine water	Algae - Skeletonema costatum	72 hours
	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2.97 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8.78 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 40000 µg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 18.4 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 13.9 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours	
Acute LC50 75000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
Acute LC50 5100 µg/l Marine water	Fish - Menidia menidia	96 hours	
Acute LC50 4.3 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
Acute LC50 9090 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
Acute LC50 9100 µg/l Fresh water	Fish - Pimephales promelas	96 hours	

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Solvent naphtha (petroleum), light aliph.	-	10 to 2500	high
Naphtha (petroleum), hydrotreated light	2.2 to 5.2	10 to 2500	high
Distillates (petroleum), light distillate hydrotreating process, low-boiling	-	10 to 2500	high
ethyl acetate	0.68	30	low
xylene	3.12	8.1 to 25.9	low
ethylbenzene	3.6	-	low

Date of issue/Date of revision

: 3/21/2024

Version : 1

Date of previous issue

: No previous validation

12/17

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS no.	Status	Reference number
ethyl acetate	141-78-6	Listed	U112
xylene	1330-20-7	Listed	U239

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1993	UN1993	UN1993	UN1993	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light aliph.)	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light aliph.)	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light aliph.)	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light aliph.)	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naphtha (petroleum), light aliph.)
Transport hazard class(es)	3 	3  	3 	3  	3 
Packing group	III	III	III	III	III

Date of issue/Date of revision : 3/21/2024

Version : 1

Date of previous issue : No previous validation

13/17

Section 14. Transport information

Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Marine Pollutant (s): Solvent naphtha (petroleum), light aliph., Naphtha (petroleum), hydrotreated light	Yes. The environmentally hazardous substance mark is not required.

Additional information

- DOT Classification** : **Reportable quantity** 1904.4 lbs / 864.6 kg [302.12 gal / 1143.7 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
- TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark).
The marine pollutant mark is not required when transported by road or rail.
- IMDG** : **Emergency schedules** F-E, _S-E_
The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- Transport in bulk according to IMO instruments** : Not available.

Section 15. Regulatory information

- U.S. Federal regulations** : **TSCA 5(a)2 final significant new use rules:** No products found.
TSCA 5(e) substance consent order: No products found.
TSCA 8(a) PAIR: heptane
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
United States inventory (TSCA 8b): All components are active or exempted.
Clean Water Act (CWA) 307: ethylbenzene; toluene
Clean Water Act (CWA) 311: xylene; ethylbenzene; toluene
- Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed
- Clean Air Act Section 602 Class I Substances** : Not listed
- Clean Air Act Section 602 Class II Substances** : Not listed
- DEA List I Chemicals (Precursor Chemicals)** : Not listed
- DEA List II Chemicals (Essential Chemicals)** : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Section 15. Regulatory information

Classification : FLAMMABLE LIQUIDS - Category 3
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A
 CARCINOGENICITY - Category 2
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
 ASPIRATION HAZARD - Category 1

Composition/information on ingredients

Name	%	Classification
Distillates (petroleum), hydro-treated light	≥25 - ≤50	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C5 through C10 and boiling in the range of approximately 35°C to 160°C (95°F to 320°F).]	≥10 - ≤25	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20°C to 190°C (- 4°F to 374°F).]	≥10 - ≤25	SKIN IRRITATION - Category 2 ASPIRATION HAZARD - Category 1
Distillates (petroleum), light distillate hydrotreating process, low-boiling ethyl acetate	≥10 - ≤25	ASPIRATION HAZARD - Category 1
	≤10	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
xylene	≤10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
ethylbenzene	≤3	ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 ASPIRATION HAZARD - Category 1

SARA 313

Date of issue/Date of revision : 3/21/2024 Version : 1
 Date of previous issue : No previous validation 15/17

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	xylene	1330-20-7	≤10
	ethylbenzene	100-41-4	≤3
Supplier notification	xylene	1330-20-7	≤10
	ethylbenzene	100-41-4	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : The following components are listed: XYLENE; DIMETHYLBENZENE; ETHYL ACETATE
- New York** : The following components are listed: Xylene mixed; Ethyl acetate
- New Jersey** : The following components are listed: XYLENES; BENZENE, DIMETHYL-; ETHYL ACETATE
- Pennsylvania** : The following components are listed: BENZENE, DIMETHYL-; ACETIC ACID ETHYL ESTER

California Prop. 65

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
ethylbenzene toluene	Yes. -	- Yes.	Cancer Developmental

Inventory list

Canada : All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

- Date of printing** : 3/21/2024
- Date of issue/ Date of revision** : 3/21/2024
- Date of previous issue** : No previous validation
- Version** : 1

- Key to abbreviations** :
- ATE = Acute Toxicity Estimate
 - BCF = Bioconcentration Factor
 - GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 - IATA = International Air Transport Association
 - IBC = Intermediate Bulk Container
 - IMDG = International Maritime Dangerous Goods
 - LogPow = logarithm of the octanol/water partition coefficient
 - MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 - N/A = Not available
 - SGG = Segregation Group
 - UN = United Nations

Date of issue/Date of revision : 3/21/2024 **Version** : 1

Date of previous issue : No previous validation 16/17

Section 16. Other information

✔ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws. Any person using this product must determine for themselves, by preliminary tests or otherwise, the suitability of this product for their purposes. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. The application, use and processing of AkzoNobel's products and the products manufactured by Buyer on the basis of AkzoNobel's technical advice are beyond AkzoNobel's control and, therefore, entirely Buyer's own responsibility. AkzoNobel makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

IA_413